

## THE NEWEST MEMBER OF THE NIGHTRIDE SCOUT SERIES

0



## **UNIQUE BENEFITS**

Animal/pedestrian detection, hunting, search + rescue, public safety, security, transport and construction, outdoor recreation, etc.

## **FEATURES**

- High resolution thermal imaging
- Remote and screen control pan + tilt
- Magnetic or permanent mount
- WiFi + Ethernet streaming to any device
- Orientation icon on screen
- Hard case included

## **TECHNICAL SPECIFICATIONS**

640-35mm 640-19mm Vehicle Specific Mounts No No Mounting Magnetic - Roof Magnetic - Roof Pan/Tilt **Remote Control Remote Control** Sealed Design **IP67 IP67 Power Consumption** 3W 3W **Power Requirement** 12-16 VDC 12-16 VDC **Operating Temperature** -40°F - +140°F -40°F - +140°F 19mm 35mm Lens Yes Yes Lens Heater 23° (H) 12° (H) **Field of View** 25hz 25hz Frames Per Sec 640 x 512 uncooled 640 x 512 uncooled Resolution Microbolometer Microbolometer **Sensor Pixel Size** 17 micron 17 micron Visibility 1600 yards 2000 yards **Optical Magnification** None None **Digital Zoom** 20 yards to 🚫 70 yards to 🚫 **Object Focus Range** 8x 8x Fixed **Focusing Mechanism** Fixed



NEW +

**IMPROVED** 

**REMOTE!** 



